

# The Art of Music Reproduction



## 5010 Mono Amplifier

### Outputs

Power Output :	200W into 8 Ohms 370W into 4 Ohms
Frequency Response :	-3dB at 52kHz, ref. 1kHz, unbalanced input
Total Harmonic Distortion :	1kHz <0.015% at 200W into 8 Ohms 1kHz <0.005% at 100W into 8 Ohms
Signal to Noise Ratio :	>120dB, A weighted, ref. 200W, 8 Ohms output >100dB A weighted, ref 1W, 8 Ohms output

### Inputs

Input Impedance :	75K Ohms at 1kHz, unbalanced input
-------------------	------------------------------------

### General

Mains Supply :	110/120V or 220/240V, 50/60Hz (factory set)
Fuse :	T10AL for 110/120V units T5AL for 220/240V units
Power Consumption :	<800W, 8 Ohms load
Dimensions (HxWxD) :	115mm x 440mm x 300mm
Net Weight :	14kg
Gross Weight :	16kg

### Features

- Large custom made toroidal transformer and screw terminal smoothing capacitors for power supply
- All bipolar transistor design using carefully selected parts
- DC coupled throughout
- Electronic, non-invasive overload protection circuit and thermal trip
- Bi-wire speaker outputs using high quality shrouded sockets
- High quality all aluminium case work
- Three year guarantee
- Available in black or titanium

