

Wilson Benesch Precision Series Loudspeaker Specifications

	P1.0	P2.0	P3.0
Description	2.5 way, floorstanding loudspeaker	2.5-way, floorstanding loudspeaker	2.5-way, floorstanding loudspeaker
Drive Technology	Tweeter : 25mm (1") Wilson Benesch Leonardo Silk Dome Tweeter Mid/Bass : 170mm (7") Wilson Benesch Tactic 2.0	Tweeter : 25mm (1") Wilson Benesch Leonardo Silk Dome Tweeter Midrange : 170mm (7") Wilson Benesch Tactic 2.0 Bass : 170mm (7") Wilson Benesch Tactic 2.0	High Bass : 170mm(7") Wilson Benesch Tactic 2.0 Tweeter : 25mm (1") Wilson Benesch Leonardo Silk Dome Tweeter Midrange : 170mm (7") Wilson Benesch Tactic 2.0 Low Bass : 170mm (7") Wilson Benesch Tactic 2.0
Crossover Technology	Tweeter : Second-Order, 5kHz High Pass Filter Mid/Bass : Directly Amplifier Coupled	Tweeter : Second-Order, 5kHz High Pass Filter Midrange : Directly Amplifier Coupled within an Acoustically Optimised Enclosure, Port Tuned with 500Hz Roll-off Bass : First-Order, with laminated high density iron cored inductors with high coil packing ratio. Ported underside of enclosure	High Bass : First-Order, Air Cored Inductor Tweeter : Second-Order, 5kHz High Pass Filter Midrange : Directly Amplifier Coupled within an Acoustically Optimised Enclosure, Port Tuned with 500Hz Roll-off Low Bass : First-Order, with laminated high density iron cored inductors with high coil packing ratio. Ported underside of enclosure
Measurements	Type : 2.5-way Impedance : 6 Ohms Nominal / 4 Ohms Minimal Sensitivity : 89dB @ 1-Meter on axis, 2.83V Input Frequency Response : 38Hz - 24kHz +/- 2dB	Type : 2.5-way Impedance : 6 Ohms Nominal / 4 Ohms Minimal Sensitivity : 89dB @ 1-Meter on axis, 2.83V Input Frequency Response : 34Hz - 24kHz +/- 2dB	Type : 2.5-way Impedance : 6 Ohms Nominal / 4 Ohms Minimal Sensitivity : 89dB @ 1-Meter on axis, 2.83V Input Frequency Response : 31Hz - 24kHz +/- 2dB
Dimensions	Height : 322mm (12.6") Cabinet // 1025mm (40.4") inc. stand Width : 205mm (8.07") Baffle // 348mm (13.7") Widest Point Foot Depth : 368mm (14.48") Weight : 30kg (66lbs) stand integrated	Height : 1105mm (43.5") Width : 205mm (8.07") Baffle // 269mm (10.6") Widest Point on Foot Depth : 472mm (18.6") Weight : 50kg (110lbs) Single Enclosure	Height : 1225mm (49.4") Width : 205mm (8.07") Baffle // 269mm (10.6") Widest Point on Foot Depth : 472mm (18.6") Weight : 59kg (130lbs) Single Enclosure
Terminations	Single-wired, located on the rear of the enclosure not the stand	Single-wired, located on the rear of the enclosure	Single-wired, located on the rear of the enclosure